



COATING PRODUCTS: Technical Data Sheet

COIL COATINGS POLYESTER

MANREZ 5 is a saturated coil coatings polyester with excellent flexibility and exterior durability. It is a hydroxyl-terminated polyester designed to be cross-linked with aminoplast resins for industrial baking enamels and coil coating applications.

Alternative Products: **MANREZ 59** offers higher application solids with superior overbake colour retention. **MANREZ 200** offers superior flexibility.

SPECIFICATIONS:

PERCENT SOLIDS	58.0 – 63.0
VISCOACITY	V - Y
ACID NUMBER	10 max. on solids
COLOUR	9 max.
SOLVENT	Solvesso 100 / Butyl Cellosolve (80/20)
MODIFIER	None

Recommended Storage: Store in a cool, dry place, preferably under 27⁰C.

MANREZ 5 is available in steel drums or bulk tanker.

BEFORE USE, ALWAYS READ AND FOLLOW THE DIRECTIONS CONTAINED ON THE LABEL, AND MATERIAL SAFETY DATA SHEET.

** The information presented, while not guaranteed, it is to the best of our knowledge true and accurate. No warranty or guarantee, express or implied, is made regarding the performance or stability of any product, since the manner of use and conditions of storage and handling are beyond our control. No suggestions for product use are intended as and nothing herein shall be construed as a recommendation to infringe any existing patents or to violate any government laws.

MANCUSO CHEMICALS LIMITED
5725 Progress St.,
Niagara Falls ON
Canada L2E 6X8
www.mancusochemicals.com



MTDSMANREZ5V3 May 19, 2009

Technical Data